

Fire-Resistant Composite Core Doors- 45-90 Minute

Neutral Pressure, Positive Pressure

Standard Models: DFMS P

Marshfield Accent Series®

Product Features
and Specifications

Interior Use Only

Thickness

1-3/4"

Maximum Size

	ITS-WH and UL		
	NP	Cat. A (PP)	Cat. A (PPFM)
Single	4/0 x 8/0	4/0 x 8/0	4/0 x 8/0
Pair	8/0 x 8/0	8/0 x 8/0	8/0 x 8/0
DE Pair	8/0 x 8/0 (45 min. only)	8/0 x 8/0	8/0 x 8/0

Hardboard available to 9/0

Minimum Size

1/5-3/4 x 6/0

Faces

- Wood Veneer
- Primed Hardboard

Crossbands

Engineered Composite

Stiles

Manufacturer's standard construction per label service listing

Rails

Manufacturer's standard construction per label service listing

Face & Core Assembly Adhesive

Per requirements of WDMA I.S. 1A, C-6

Core

Fire-resistant composite per label service listing

Lite Openings

See Appendix I

Factory Finish

- Enviroclad UV® finish
- Prime
- Opaque

Warranty

5-year. No exterior warranty
Option: Full; life of original installation. No exterior warranty

Environmental Options & LEED Credit Contribution

(Not all credits may be available
with some constructions)

- MR 4-Recycled Content- all models

The mark of excellence™



Note: Marshfield DoorSystems doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.