



For Warranty or Label
 A - Minimum Stile or Rail Dimension
 B - Minimum Lite to Lock Dimension
 C - Minimum Lite to Lite Dimension

Door Type	Fire Rating	A	B	C
ParticleBoard	0	5	3¼	3¼
Stave	0	5	3¼	3¼
SCL	0	5	1¼	3
ParticleBoard	20	5 ½	3¼	3¼
Stave	20	5 ½	3¼	3¼
SCL	20	5 ½	1¼	3¼
Mineral or Fire Core	45-90	5 ½	3¼	3¼

Weights

Approximate Weights per Square Foot by Door Type

- 1-3/4" Particleboard Core5.5 lbs
- 1-3/8" Particleboard Core4.4 lbs
- 1-3/4" Mineral Core (45, 60, 90-minute)3.7 lbs
- 1-3/4" Structural Composite Lumber Core6.9 lbs
- 1-3/4" Staved Core4.6 lbs
- 2-1/4" Staved Core5.9 lbs
- 1-3/4" Sound Retardant (DSR41)7.1 lbs
- 1-3/4" Stile and Rail6.0 lbs
- 1-3/4" Radiation Shielded 1/16" Lead Lined9.5 lbs
- 1-3/4" Extra Heavy Duty Particle Board8.0 lbs

The mark of excellence™ 

Note: Marshfield DoorSystems doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.