PerfectMatch™ Fire-Rated Mineral Core Doors

Positive Pressure with Concealed Intumescents

90 - MINUTE (PMD-90PP), 60-MINUTE (PMD-60PP), 45-MINUTE (PMD-45PP) (13)

Product Features and Specifications	Interior Use Only
Thickness	1-3/4"
Maximum Size	**ITS-WH and UL: Single:** 4/0 x 8/0 **Pair:** 8/0 x 8/0 **(57)** **Double Egress Pair:** 8/0 x 8/0 **(57)**
Minimum Size	1-5 ¾ x 6/0
Faces	Thermoset Polymer
Crossbands	Engineered Fiber
Stiles	Flamesafe Plus or Concealed intumescent positive pressure stiles with edge banding or stained stiles to match face. **Single:** 17/32" **Pair:** 2-1/4" **Double Egress Pair: Lock:** 5-3/4" **Hinge:** 2-1/4"
Top and Bottom Rails (24,25)	**Single: Top:** 7/8 AT **Bottom:** 2-1/16" AT **Pair: Top:** 1-3/4" Tectonite **Bottom:** 1-3/4" Tectonite **Double Egress Pair: Top:** 3-3/8" Tectonite **Bottom:** 3-3/8" Tectonite
Core Assembly Adhesive	Type II (water-resistant)
Core	Asbestos-free incombustible mineral **(34)**
Lite Openings (6)	Metal Vision Frames Only See Glazing Table
Other Detail Work (7,21,35)	• Fitting • Machining • Fusible Link Louvers
Warranty	Limited Lifetime

***Refer to seperate page for explanation of footnotes.**

Note: Marshfield DoorSystems, Inc. doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.