

# PerfectMatch™ Fire-Rated Particleboard Core Doors

Positive Pressure with Concealed Intumescents (PMP-45PP) (13)

## Product Features and Specifications

## Interior Use Only

<b>Thickness</b>	1-3/4"
<b>Maximum Size</b>	<b>ITS-WH and UL:</b> <b>Single:</b> 4/0 x 8/0 <b>Standard Pair:</b> 6/0 x 7/0
<b>Minimum Size</b>	1-5 ¾ x 6/0
<b>Faces</b>	Thermoset Polymer
<b>Crossbands</b>	Engineered Fiber
<b>Stiles</b>	15/16" MDF Rated stile with edge band to match face.
<b>Top and Bottom Rails</b>	1" MDF Rated
<b>Core Assembly Adhesive</b>	Type II (water-resistant)
<b>Core</b>	UNI-COR FR Particleboard
<b>Lite Openings (6)</b>	Area = 1296 sq. in.    Width = 36"    Height = 54" with approved MVF intumescent along cutout.
<b>Other Detail Work (40,63,64,66)</b>	<ul style="list-style-type: none"><li>• Fitting    • Butt Hinges    • Mortise or Cylindrical Locks</li><li>• Kickplates    • Surface Mounted Hardware    • Dead Bolts</li></ul>
<b>Warranty</b>	Limited Lifetime

\*Refer to separate page for explanation of footnotes.