

Harmony Jambs and Casings

Non-rated & 20 MinuteWood Jamb Sets

Technical Information

Species Standard species for 20 minute rated frames are Red Oak, White Oak, Natural Birch, Cherry, African Mahogany, and HardMaple.

On special order, any commercially available species with density equal to or greater than 33.4 lbs/cubicft. Any species can be specified for non-rated frames.

Sizes Maximum for 20 minute label is 4'0" x 9'0" (1220 x 2740mm) for single doors and 8'0"x 9'0" (2440 x 2740mm) for regular swing pair doors. Non-label framesare available in larger sizes.

Wall thickness minimum 3 3/4" (95mm). Jambs maybe made from edge-glued lumber when wall thickness exceeds width of available lumber.

Wall conditions Wood stud, steel stud,or masonry.

Profiles:

Applied T-Stop (ploughed-in-stop) standard 3/4" thick.

Single Rabbet and Double Rabbet 1 1/8" thick are optional.

Profile type should be noted at the time of quote request.

Casing Standard or custom profile casing available with frames. Minimumsize 1/2" x 1 1/2",1(113x 38mm), any species with density equal to or greater than Mahogany (33.4PCF). Casing maybe supplied by others but must meet minimum size and density requirements. Non rated frames have no restrictions for the casing.

Hardware machining available with hinge and strike machining as well as other hardware preparation. Fire rated frames must be machined for hardware at the factory or by a licensed machiner before they canbe labeled.

Finishing available to match the door manufacturers' standard or custom colors. Also available primed or sealed only. Paint finishes are not available.

Warranty for interior applications, life of original installation against manufacturers' defects. Exterior applications not recommended or warranted.

Label service 20 minute listed and labeled by Intertek Tertek Testing Services- Wamock Hersey. And UL (Positive Pressure) UBC7-2-1997.

The mark of excellence™ 

Note: Marshfield DoorSystems doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.

For more information call: 800-869-3667
©2010 Marshfield DoorSystems, Inc.

 **Marshfield®**
DoorSystems